



Chint DDSU666

Single-phase DIN-Rail Smart Meter

High accuracy and low consumption
Bi-direction measurement
DIN-Rail installation

Nominal voltage (Un): 120V, 220V, 230V, 240V
Operating range: 0.7Un~1.2Un
Power consumption: ≤1W, 5VA
CT / DC current: 1.5(6)A / 5(80)A
Frequency: 50Hz / 60Hz
Communication interface: RS485
Communication protocol: Modbus, DL/T
LCD display: 24x14 mm
Weight: 200 g
Dimensions (WxDxH): 36x65x98 mm



Chint DTSU666

Three-phase DIN-Rail Smart Meter

High accuracy and low consumption
Bi-direction measurement
DIN-Rail installation

Nominal voltage (Un): 3x220/380V, 3x57.7/100V
Operating range: 0.7Un~1.2Un
Power consumption: ≤1W, 5VA
CT / DC current: 1.5(6)A / 5(80)A
Frequency: 50Hz / 60Hz
Communication interface: RS485
Communication protocol: Modbus, DL/T
LCD display: 48x16 mm
Weight: 400 g
Dimensions (WxDxH): 72x65x98 mm



Solarman LSW-5

Stick Logger

Independent module, protecting internal parts of inverter
Plug and play, no extra power supply is required
Waterproof design, resistant to bad weather

Communication: GPRS, WiFi, 4G, Ethernet and others
Data interface: RS485/RS232/TTL/USB and others
Antenna: Internal antenna
Working voltage: DC 5-12V
Working power: 1.5W
Dimensions (WxDxH): 46x30x118 mm